




## NUMINOS® MOVE L

Recessed ceiling light, 4000 K, 55°, IP20, round, white

Design, technology and function in perfection: NUMINOS is the light system from SLV that combines everything. This way, you can experience a thousand lighting design possibilities with a variety of downlights and spotlights. This also includes NUMINOS® MOVE DL L, which impresses as a recessed ceiling light with the best workmanship and lighting quality. Ideal for discreet, modern and space-saving lighting that directs the accent to objects or the room. The recessed ceiling light convinces with a power consumption of 17 watts, luminous flux of 2700 lumens, colour temperature of 4000 Kelvin and a colour reproduction index of 90. Installation is then done in no time at all. When do you choose NUMINOS® from SLV?



## TECHNICAL DATA

|                                   |                         |
|-----------------------------------|-------------------------|
| Item no.                          | 1009862                 |
| Number of different light outlets | 1                       |
| Rotating or tilting               | rotary bar and tiltable |
| IP Code                           | IP20                    |
| Assembly                          | Recessed                |
| Assembly details                  | Ceiling                 |
| Secondary power / voltage         | 500 mA                  |
| Safety class                      | III                     |
| Wattage                           | 17 W                    |
| Minimum ambient temperature       | -20 °C                  |
| Maximum ambient temperature       | 40 °C                   |
| Lumen                             | 2700 lm                 |
| Colour temperature                | 4000 Kelvin             |
| Beam angle                        | 55 °                    |
| Color                             | white                   |
| CRI                               | 90                      |
| UGR ≤                             | 22                      |
| Service life                      | 50000 h                 |
| Risk Group                        | 1                       |
| Height                            | 9.3 cm                  |
| Diameter                          | 16 cm                   |
| Net weight                        | 0.51 kg                 |

## Light Source

|         |   |
|---------|---|
| 2093752 |  |
|---------|---|

### Accessories

|         |  |
|---------|--|
| 1006148 | Numinos® L Reducing ring , round 240/150 mm white  |
| 1006149 | Numinos® L Reducing ring , square 240/150 mm black |
| 1010689 | NUMINOS® L , Frosted diffuser                      |
| 1010697 | LED driver , 21W, 500 mA                           |
| 1010687 | NUMINOS® L , Honeycomb diffuser                    |
| 1010701 | LED driver , 19 W, 500 mA, PHASE                   |
| 1010688 | NUMINOS® L , Prismatic diffuser                    |
| 1006150 | Numinos® L Reducing ring , square 240/150 mm white |
| 1006147 | Numinos® L Reducing ring , round 240/150 mm black  |
| 1010690 | NUMINOS® L , Elliptical diffuser                   |
| 1010705 | LED driver , 36W, 500 mA, DALI                     |
| 1010132 | NUMINOS® L , reflector, copper                     |
| 1010131 | NUMINOS® L , reflector, gold                       |

|                       |         |
|-----------------------|---------|
| Gross weight          | 0.66 kg |
| Shape of cut-out      | round   |
| Installation depth    | 10.5 cm |
| Installation diameter | 14.5 cm |
| BIG WHITE Page        | 41      |