




NUMINOS® GIMBLE XL

Recessed ceiling light, 2700 K, 55°, white

Design, technology and function in perfection: NUMINOS is the light system from SLV that combines everything. With various downlights and spotlights, you can experience a thousand lighting design possibilities. Like with the NUMINOS® GIMBLE XL recessed ceiling light, which impresses with its high-quality workmanship and light. Ideal for harmonious, modern and space-saving lighting that directs the accent to objects or the room. This means that easy installation is a mere formality. When will you choose SLV's modular variety?



TECHNICAL DATA

Item no.	1009880
Number of different light outlets	1
Rotating or tilting	rotary bar and tiltable
IP Code	IP20
Assembly	Recessed
Assembly details	Ceiling
Secondary power / voltage	700 mA
Safety class	III
Wattage	24 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Lumen	3500 lm
Colour temperature	2700 Kelvin
Beam angle	55 °
Color	white
CRI	90
UGR ≤	22
Service life	50000 h
Risk Group	1
Height	13.5 cm
Diameter	19 cm
Net weight	0.85 kg

Light Source

2093865	
---------	---

Accessories

1010698	LED driver , 30W, 700 mA
1006152	Numinos® XL Reducing ring , round 240/180 mm white
1010706	LED driver , 36W, 700 mA, DALI
1006151	Numinos® XL Reducing ring , round 240/180 mm black
1010694	NUMINOS® XL , Elliptical diffuser
1010692	NUMINOS® XL , Prismatic diffuser
1006154	Numinos® XL Reducing ring , square 240/180 mm white
1010702	LED driver , 30W, 700 mA, PHASE
1010693	NUMINOS® XL , Frosted diffuser
1006153	Numinos® XL Reducing ring , square 240/180 mm black
1010691	NUMINOS® XL , Honeycomb diffuser
1010133	NUMINOS® XL , reflector, gold
1010134	NUMINOS® XL , reflector, copper

Gross weight	1.1 kg
Shape of cut-out	round
Installation depth	13.5 cm
Installation diameter	17.5 cm
BIG WHITE Page	53