




NUMINOS® GIMBLE XL

Recessed ceiling light, 3000 K, 20°, white

The NUMINOS light system from SLV skilfully combines function, design and technology. This way, you can experience a thousand lighting design possibilities with different downlights and spotlights. Also with the NUMINOS® GIMBLE XL recessed ceiling light, which convinces with the best workmanship and lighting quality. Ideal for harmonious, modern and space-saving lighting that directs the accent to objects or the room. This means that simple installation is a mere formality. When to choose NUMINOS from SLV – modular diversity awaits you.



TECHNICAL DATA

| | |
|-----------------------------------|-------------------------|
| Item no. | 1009892 |
| Number of different light outlets | 1 |
| Rotating or tilting | rotary bar and tiltable |
| IP Code | IP20 |
| Assembly | Recessed |
| Assembly details | Ceiling |
| Secondary power / voltage | 700 mA |
| Safety class | III |
| Wattage | 24 W |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 40 °C |
| Lumen | 3600 lm |
| Colour temperature | 3000 Kelvin |
| Beam angle | 20 ° |
| Color | white |
| CRI | 90 |
| UGR ≤ | 19 |
| Service life | 50000 h |
| Risk Group | 1 |
| Height | 13.5 cm |
| Diameter | 19 cm |
| Net weight | 0.85 kg |

Light Source

| | |
|---------|---|
| 2093861 |  |
|---------|---|

Accessories

| | |
|---------|---|
| 1010698 | LED driver , 30W, 700 mA |
| 1006152 | Numinos® XL Reducing ring , round 240/180 mm white |
| 1010706 | LED driver , 36W, 700 mA, DALI |
| 1006151 | Numinos® XL Reducing ring , round 240/180 mm black |
| 1010694 | NUMINOS® XL , Elliptical diffuser |
| 1010692 | NUMINOS® XL , Prismatic diffuser |
| 1006154 | Numinos® XL Reducing ring , square 240/180 mm white |
| 1010702 | LED driver , 30W, 700 mA, PHASE |
| 1010693 | NUMINOS® XL , Frosted diffuser |
| 1006153 | Numinos® XL Reducing ring , square 240/180 mm black |
| 1010691 | NUMINOS® XL , Honeycomb diffuser |
| 1010133 | NUMINOS® XL , reflector, gold |
| 1010134 | NUMINOS® XL , reflector, copper |

| | |
|-----------------------|---------|
| Gross weight | 1.1 kg |
| Shape of cut-out | round |
| Installation depth | 13.5 cm |
| Installation diameter | 17.5 cm |
| BIG WHITE Page | 53 |