




NUMINOS® XL

Recessed ceiling light, 3000 K, 20°, IP20, round, black

NUMINOS is the perfectly coordinated light system from SLV that combines function, design and technology. With a variety of downlights and spotlights, you provide a thousand lighting design options. Also with the NUMINOS® DL XL recessed ceiling light, which convinces with the best workmanship and lighting quality. Ideal for harmonious, modern and space-saving lighting that directs the accent to objects or the room. The recessed ceiling light has a power consumption of 24 watts, a luminous flux of 3600 lumens, a colour temperature of 3000 Kelvin and a good colour reproduction index of over 90. This means that easy installation is a mere formality. When to choose NUMINOS from SLV – modular diversity awaits you.



TECHNICAL DATA

Item no.	1009936
Number of different light outlets	1
IP Code	IP20
Assembly	Recessed
Assembly details	Ceiling
Secondary power / voltage	700 mA
Safety class	III
Wattage	24 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Lumen	3600 lm
Colour temperature	3000 Kelvin
Beam angle	20 °
Color	black
CRI	90
UGR ≤	19
Service life	50000 h
Risk Group	1
Height	10.5 cm
Diameter	16 cm
Net weight	0.704 kg
Gross weight	0.8 kg

Light Source

2093861	
---------	---

Accessories

1010698	LED driver , 30W, 700 mA
1006148	Numinos® L Reducing ring , round 240/150 mm white
1006149	Numinos® L Reducing ring , square 240/150 mm black
1010706	LED driver , 36W, 700 mA, DALI
1010694	NUMINOS® XL , Elliptical diffuser
1010692	NUMINOS® XL , Prismatic diffuser
1006150	Numinos® L Reducing ring , square 240/150 mm white
1006147	Numinos® L Reducing ring , round 240/150 mm black
1010702	LED driver , 30W, 700 mA, PHASE
1010693	NUMINOS® XL , Frosted diffuser
1010691	NUMINOS® XL , Honeycomb diffuser
1010133	NUMINOS® XL , reflector, gold
1010134	NUMINOS® XL , reflector, copper

Shape of cut-out	round
Installation depth	10.5 cm
Installation diameter	14.5 cm
BIG WHITE Page	33