


## NUMINOS® MOVE XL

Recessed ceiling light, 2700 K, 40°, IP20, round, white

The NUMINOS light system from SLV skilfully combines function, design and technology. This way, you can experience a thousand lighting design possibilities with different downlights and spotlights. This also includes NUMINOS® MOVE DL XL, which impresses as a recessed ceiling light with the best workmanship and lighting quality. Ideal for unobtrusive, modern and space-saving lighting that draws the focus to objects or the room. The recessed ceiling light convinces with a power consumption of 24 watts, luminous flux of 3500 lumens, colour temperature of 2700 Kelvin and a colour reproduction index of 90. This means that easy installation is a mere formality. When to choose NUMINOS from SLV – modular diversity awaits you.



## TECHNICAL DATA

|                                   |                         |
|-----------------------------------|-------------------------|
| Item no.                          | 1009985                 |
| Number of different light outlets | 1                       |
| Rotating or tilting               | rotary bar and tiltable |
| IP Code                           | IP20                    |
| Assembly                          | Recessed                |
| Assembly details                  | Ceiling                 |
| Secondary power / voltage         | 700 mA                  |
| Safety class                      | III                     |
| Wattage                           | 24 W                    |
| Minimum ambient temperature       | -20 °C                  |
| Maximum ambient temperature       | 40 °C                   |
| Lumen                             | 3500 lm                 |
| Colour temperature                | 2700 Kelvin             |
| Beam angle                        | 40 °                    |
| Color                             | white                   |
| CRI                               | 90                      |
| UGR ≤                             | 19                      |
| Service life                      | 50000 h                 |
| Risk Group                        | 1                       |
| Height                            | 11.6 cm                 |
| Diameter                          | 19 cm                   |
| Net weight                        | 0.63 kg                 |

## Light Source

|         |   |
|---------|---|
| 2093865 |  |
|---------|---|

### Accessories

|         |   |
|---------|---|
| 1010698 | LED driver , 30W, 700 mA                            |
| 1006152 | Numinos® XL Reducing ring , round 240/180 mm white  |
| 1010706 | LED driver , 36W, 700 mA, DALI                      |
| 1006151 | Numinos® XL Reducing ring , round 240/180 mm black  |
| 1010694 | NUMINOS® XL , Elliptical diffuser                   |
| 1010692 | NUMINOS® XL , Prismatic diffuser                    |
| 1006154 | Numinos® XL Reducing ring , square 240/180 mm white |
| 1010702 | LED driver , 30W, 700 mA, PHASE                     |
| 1010693 | NUMINOS® XL , Frosted diffuser                      |
| 1006153 | Numinos® XL Reducing ring , square 240/180 mm black |
| 1010691 | NUMINOS® XL , Honeycomb diffuser                    |
| 1010133 | NUMINOS® XL , reflector, gold                       |
| 1010134 | NUMINOS® XL , reflector, copper                     |

|                       |         |
|-----------------------|---------|
| Gross weight          | 1 kg    |
| Shape of cut-out      | round   |
| Installation depth    | 13 cm   |
| Installation diameter | 17.5 cm |
| BIG WHITE Page        | 43      |