




NUMINOS® GIMBLE XS

Recessed ceiling light, 2700 K, 40°, IP20, round, black

The NUMINOS light system from SLV perfectly combines function, design and technology. With different downlights and spotlights, you can experience a thousand lighting design possibilities. Also with the NUMINOS® GIMBLE XS recessed ceiling light, which convinces with the best workmanship and lighting quality. Ideal for discreet, modern and space-saving lighting that draws the focus to objects or the room. This means that simple installation is a mere formality. When do you choose NUMINOS ® from SLV?



TECHNICAL DATA

Item no.	1010029
Number of different light outlets	1
Rotating or tilting	rotary bar and tiltable
IP Code	IP20
Assembly	Recessed
Assembly details	Ceiling
Secondary power / voltage	200 mA
Safety class	III
Wattage	6.9 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Lumen	900 lm
Colour temperature	2700 Kelvin
Beam angle	40 °
Color	black
CRI	90
UGR ≤	22
Service life	50000 h
Risk Group	1
Height	5.7 cm
Diameter	8 cm
Net weight	0.11 kg

Light Source

2093755	
---------	-----------------------------------------------------------------------------------

Accessories

1006136	Numinos® XS Reducing ring , round 160/70 mm white
1006135	Numinos® XS Reducing ring , round 160/70 mm black
1005614	NUMINOS® XS , frosted diffuser
1010695	LED driver , 21W, 200 mA, DALI
1010703	LED driver , 23W, 200 mA, DALI
1005612	NUMINOS® XS , diffuser
1010699	LED driver , 10W, 200 mA, PHASE
1005615	NUMINOS® XS , black diffuser
1006137	Numinos® XS Reducing ring , square 160/70 mm black
1006138	Numinos® XS Reducing ring , square 160/70 mm white
1005613	NUMINOS® XS , transparent diffuser
1010126	NUMINOS® XS , reflector, copper
1010125	NUMINOS® XS , reflector, gold

Gross weight	0.21 kg
Shape of cut-out	round
Installation depth	8 cm
Installation diameter	6.8 cm
BIG WHITE Page	45