


## FLATT II

Wall-mounted light, PHASE, 2700 K, 9.5W, anthracite / brown

The FLATT II light range combines modern design with high functionality. The wall-mounted and bollard lights are ideal for accentuated façade and path lighting. With a sea air resistant coating, dark sky compliant light distribution (ULOR <2%), 2,700K warm white light and optional sensor technology, they offer flexible solutions for residential and HoReCa applications.



## TECHNICAL DATA

Item no.	1010101
Number of different light outlets	2
IP Code	IP65
Impact resistance class	IK 03
Impact resistance	0.35 Joule
Assembly	Surface
Assembly details	Wall
Dimmable	Yes
Dimming technology	Leading edge, trailing edge
Number of through-wires	130
Primary nominal voltage	220-240V ~50/60 Hz
Secondary power / voltage	240 mA
Safety class	I
Wattage	9.5 W
Minimum ambient temperature	-25 °C
Maximum ambient temperature	45 °C
Number of luminaires at LS B16A	210
Number of luminaires at LS C16A	210
Level of inrush current	4.1 A
Duration of inrush current	81 µs
Temperature at glass (light emission)	59 °C
Lumen	640 lm

## Light Source

916561	
--------	---

<b>Colour temperature</b>	2700 Kelvin
<b>Color</b>	anthracite/brown
<b>CRI</b>	80
<b>Service life</b>	50000 h
<b>Risk Group</b>	1
<b>Width</b>	9.85 cm
<b>Height</b>	26 cm
<b>Depth</b>	8.56 cm
<b>Net weight</b>	1.16 kg
<b>Gross weight</b>	1.37 kg
<b>BIG WHITE Page</b>	858