




FLATT II

Wall-mounted light, PHASE, 2700 K, 9.5W, black

The FLATT II light range combines modern design with high functionality. The wall-mounted and bollard lights are ideal for accentuated façade and path lighting. With a sea air resistant coating, dark sky compliant light distribution (ULOR <2%), 2,700K warm white light and optional sensor technology, they offer flexible solutions for residential and HoReCa applications.



TECHNICAL DATA

| | |
|---------------------------------------|-----------------------------|
| Item no. | 1010102 |
| Number of different light outlets | 2 |
| IP Code | IP65 |
| Impact resistance class | IK 03 |
| Impact resistance | 0.35 Joule |
| Assembly | Surface |
| Assembly details | Wall |
| Dimmable | Yes |
| Dimming technology | Leading edge, trailing edge |
| Number of through-wires | 130 |
| Primary nominal voltage | 220-240V ~50/60 Hz |
| Secondary power / voltage | 240 mA |
| Safety class | I |
| Wattage | 9.5 W |
| Minimum ambient temperature | -25 °C |
| Maximum ambient temperature | 45 °C |
| Number of luminaires at LS B16A | 210 |
| Number of luminaires at LS C16A | 210 |
| Level of inrush current | 4.1 A |
| Duration of inrush current | 81 µs |
| Temperature at glass (light emission) | 59 °C |
| Lumen | 620 lm |

Light Source

| | |
|--------|---|
| 916561 |  |
|--------|---|

| | |
|---------------------------|-------------|
| Colour temperature | 2700 Kelvin |
| Color | black |
| CRI | 80 |
| Service life | 50000 h |
| Risk Group | 1 |
| Width | 9.85 cm |
| Height | 26 cm |
| Depth | 8.56 cm |
| Net weight | 1.1 kg |
| Gross weight | 1.32 kg |
| BIG WHITE Page | 858 |