



HELIA PRO L

Wall-mounted light, up/down, DALI, P1, 2700 K, 20W, Touch, 24°, white

The HELIA PRO wall light range offers flexible solutions for accentuating façades with two housing sizes and two wattage classes, either as single or up/down lighting. Efficient LED technology, DALI control, precise light distribution and resistance to sea air enable high-quality architectural lighting in outdoor areas.

TECHNICAL DATA

| | |
|---------------------------------------|--------------------|
| Item no. | 1010172 |
| Number of different light outlets | 2 |
| IP Code | IP65 |
| Impact resistance class | IK 08 |
| Impact resistance | 5 Joule |
| Assembly | Surface |
| Assembly details | Wall |
| Dimmable | Yes |
| Dimming technology | DALI |
| Number of through-wires | 40 |
| Primary nominal voltage | 220-240V ~50/60 Hz |
| Secondary power / voltage | 500 mA |
| Safety class | I |
| Wattage | 20 W |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 45 °C |
| Number of luminaires at LS B16A | 40 |
| Number of luminaires at LS C16A | 60 |
| Level of inrush current | 30 A |
| Duration of inrush current | 100 µs |
| Temperature at glass (light emission) | 55 °C |
| Lumen | 2400 lm |

Light Source

| | |
|--|---|
| |  |
|--|---|

Accessories

| | |
|---------|--|
| 1010940 | Reflector L 10° , for THEO PRO and HELIA PRO |
|---------|--|

| | |
|--------------------|-------------|
| Colour temperature | 2700 Kelvin |
| Beam angle | 24 ° |
| Color | white |
| CRI | 80 |
| Service life | 50000 h |
| Risk Group | 1 |
| Height | 30.5 cm |
| Depth | 15.5 cm |
| Diameter | 10.8 cm |
| Net weight | 1.91 kg |
| Gross weight | 2.5 kg |
| BIG WHITE Page | 875 |