



HELIA PRO L

Wall-mounted light, single, DALI, P2, cylindrical, 2700 K, 15W, 24°, white

The HELIA PRO wall light range offers flexible solutions for accentuating façades with two housing sizes and two wattage classes, either as single or up/down lighting. Efficient LED technology, DALI control, precise light distribution and resistance to sea air enable high-quality architectural lighting in outdoor areas.

TECHNICAL DATA

Item no.	1010174
Number of different light outlets	1
IP Code	IP65
Impact resistance class	IK 08
Impact resistance	5 Joule
Assembly	Surface
Assembly details	Wall
Dimmable	Yes
Dimming technology	DALI
Number of through-wires	15
Primary nominal voltage	220-240V ~50/60 Hz
Secondary power / voltage	380 mA
Safety class	I
Wattage	15 W
Minimum ambient temperature	-25 °C
Maximum ambient temperature	45 °C
Number of luminaires at LS B16A	15
Number of luminaires at LS C16A	24
Level of inrush current	65 A
Duration of inrush current	200 µs
Temperature at glass (light emission)	55 °C
Lumen	1800 lm

Light Source

	
--	-----------------------------------------------------------------------------------

Accessories

1010940	
---------	--

Colour temperature	2700 Kelvin
Beam angle	24 °
Color	white
CRI	80
Service life	50000 h
Risk Group	1
Height	30.5 cm
Depth	15.5 cm
Diameter	10.8 cm
Net weight	1.62 kg
Gross weight	2.2 kg
BIG WHITE Page	877