




THEO PRO S

Wall-mounted light, single, DALI, P2, rectangular, 2700 K, 6W, 24°, white

The THEO PRO wall light series combines a clear, square design with modern technology for precise accent lighting. Available in two sizes and performance classes, with single or up/down light, they offer versatile solutions for modern façade lighting in outdoor areas thanks to DALI control and resistance to sea air.



TECHNICAL DATA

Item no.	1010182
Number of different light outlets	1
IP Code	IP65
Impact resistance class	IK 06
Impact resistance	1 Joule
Assembly	Surface
Assembly details	Wall
Dimmable	Yes
Dimming technology	DALI
Number of through-wires	15
Primary nominal voltage	220-240V ~50/60 Hz
Secondary power / voltage	150 mA
Safety class	I
Wattage	6 W
Minimum ambient temperature	-25 °C
Maximum ambient temperature	45 °C
Number of luminaires at LS B16A	15
Number of luminaires at LS C16A	24
Level of inrush current	65 A
Duration of inrush current	200 µs
Temperature at glass (light emission)	56 °C
Lumen	600 lm

Light Source

1028936	
---------	-----------------------------------------------------------------------------------

Accessories

1010939	
---------	--

Colour temperature	2700 Kelvin
Beam angle	24 °
Color	white
CRI	80
Service life	50000 h
Risk Group	1
Width	6.5 cm
Height	17.5 cm
Depth	10 cm
Net weight	0.82 kg
Gross weight	1.03 kg
BIG WHITE Page	869