



## THEO PRO S

Wall-mounted light, up/down, DALI, P2, rectangular, 2700 K, 12W, 24°, white

The THEO PRO wall light series combines a clear, square design with modern technology for precise accent lighting. Available in two sizes and performance classes, with single or up/down light, they offer versatile solutions for modern façade lighting in outdoor areas thanks to DALI control and resistance to sea air.

### TECHNICAL DATA

Item no.	1010184
Number of different light outlets	2
IP Code	IP65
Impact resistance class	IK 06
Impact resistance	1 Joule
Assembly	Surface
Assembly details	Wall
Dimmable	Yes
Dimming technology	DALI
Number of through-wires	15
Primary nominal voltage	220-240V ~50/60 Hz
Secondary power / voltage	300 mA
Safety class	I
Wattage	12 W
Minimum ambient temperature	-25 °C
Maximum ambient temperature	45 °C
Number of luminaires at LS B16A	15
Number of luminaires at LS C16A	24
Level of inrush current	65 A
Duration of inrush current	200 µs
Temperature at glass (light emission)	56 °C
Lumen	1200 lm

## Light Source

1028936	
---------	---

## Accessories

1010939	
---------	--

<b>Colour temperature</b>	2700 Kelvin
<b>Beam angle</b>	24 °
<b>Color</b>	white
<b>CRI</b>	80
<b>Service life</b>	50000 h
<b>Risk Group</b>	1
<b>Width</b>	6.5 cm
<b>Height</b>	17.5 cm
<b>Depth</b>	10 cm
<b>Net weight</b>	0.94 kg
<b>Gross weight</b>	1.15 kg
<b>BIG WHITE Page</b>	869