



TAHA II 70

Free-standing lamp, PHASE, 2200/2700 K, IP65, cylindrical, black

The TAHA II series of lights impresses with its timeless retro design, tinted glass and efficient LED technology. Whether as a wall light or cylindrical free-standing light in three heights, it provides warm light (2,200 K / 2,700 K), is resistant to sea air and is ideal for private outdoor areas thanks to the sensor with primary/slave functionality.

TECHNICAL DATA

Item no.	1010198
Number of different light outlets	1
IP Code	IP65
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Assembly	Surface
Assembly details	Ground
Dimmable	Yes
Dimming technology	Leading edge, trailing edge
Primary nominal voltage	220-240V ~50/60 Hz
Secondary power / voltage	240 mA
Safety class	I
Wattage	10 W
Minimum ambient temperature	-25 °C
Maximum ambient temperature	45 °C
Number of luminaires at LS B16A	250
Number of luminaires at LS C16A	250
Level of inrush current	3.28 A
Duration of inrush current	67.2 µs
Lumen	450 / 500 lm
Colour temperature	2200/2700 Kelvin
Color	black

Light Source

2432928	
---------	---

CRI	80
Service life	50000 h
Width	15 cm
Height	70.2 cm
Depth	15 cm
Net weight	1.61 kg
Gross weight	2.12 kg
BIG WHITE Page	763