


KALU 2.0

1~ spot, PHASE, cylindrical, 3000 K, 10W, 36°, black

KALU 2.0 presents the decorative lighting classic in a new look. The clear design with interchangeable front rings and four lens options (15°, 24°, 36°, 60°) offers maximum flexibility in lighting design. With an efficiency of over 140 lm/W, a low UGR <19, modern colour combinations and precise LED technology, KALU 2.0 fits perfectly into living spaces, restaurants and modern offices.



TECHNICAL DATA

| | |
|-----------------------------------|--------------------|
| Item no. | 1010226 |
| Number of different light outlets | 1 |
| IP Code | IP20 |
| Impact resistance class | IK 02 |
| Impact resistance | 0.2 Joule |
| Assembly details | Ceiling |
| Dimmable | Yes |
| Dimming technology | trailing edge |
| Primary nominal voltage | 220-240V ~50/60 Hz |
| Secondary power / voltage | 250 mA |
| Safety class | II |
| Wattage | 10 W |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 40 °C |
| Number of luminaires at LS B16A | 44 |
| Number of luminaires at LS C16A | 89 |
| Level of inrush current | 25 A |
| Duration of inrush current | 100 µs |
| Lumen | 1450 lm |
| Colour temperature | 3000 Kelvin |
| Beam angle | 36 ° |
| Color | black |

Light Source

| | |
|---------|---|
| 2093784 |  |
|---------|---|

Accessories

| | |
|---------|------------------------------------|
| 1010140 | KALU 2.0 , lens, 15° |
| 1010141 | KALU 2.0 , lens, 24° |
| 1010142 | KALU 2.0 , lens, 36° |
| 1010143 | KALU 2.0 , lens, 60° |
| 1010139 | KALU 2.0 , decorative ring, copper |
| 1010136 | KALU 2.0 , decorative ring, black |
| 1010135 | KALU 2.0 , decorative ring, white |
| 1010138 | KALU 2.0 , decorative ring, gold |

| | |
|----------------|---------|
| CRI | 90 |
| UGR ≤ | 19 |
| Service life | 50000 h |
| Risk Group | 1 |
| Length | 17.7 cm |
| Width | 4.8 cm |
| Height | 12.7 cm |
| Net weight | 0.56 kg |
| Gross weight | 0.7 kg |
| BIG WHITE Page | 565 |