


## KALU 2.0

Wall and ceiling-mounted light, PHASE, 3000 K, 10W, 36°, black

KALU 2.0 presents the decorative lighting classic in a new look. The clear design with interchangeable front rings and four lens options (15°, 24°, 36°, 60°) offers maximum flexibility in lighting design. With an efficiency of over 140 lm/W, a low UGR <19, modern colour combinations and precise LED technology, KALU 2.0 fits perfectly into living spaces, restaurants and modern offices.



## TECHNICAL DATA

Item no.	1010261
Number of different light outlets	1
IP Code	IP20
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Assembly	Surface
Assembly details	Ceiling,Wall
Dimmable	Yes
Dimming technology	trailing edge
Primary nominal voltage	220-240V ~50/60 Hz
Secondary power / voltage	250 mA
Safety class	I
Wattage	10 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Number of luminaires at LS B16A	98
Number of luminaires at LS C16A	123
Level of inrush current	8.5 A
Duration of inrush current	60 µs
Lumen	1450 lm
Colour temperature	3000 Kelvin
Beam angle	36 °

## Light Source

2093784	
---------	---

## Accessories

1010140	KALU 2.0 , lens, 15°
1010141	KALU 2.0 , lens, 24°
1010142	KALU 2.0 , lens, 36°
1010143	KALU 2.0 , lens, 60°
1010139	KALU 2.0 , decorative ring, copper
1010136	KALU 2.0 , decorative ring, black
1010135	KALU 2.0 , decorative ring, white
1010138	KALU 2.0 , decorative ring, gold

Color	black
CRI	90
UGR ≤	19
Service life	50000 h
Risk Group	1
Height	9 cm
Diameter	9 cm
Net weight	0.56 kg
Gross weight	0.66 kg
BIG WHITE Page	403