



SIGHT EVO

3~ spot, DALI, double, rectangular, 3000K, 25W, 60°, black

SIGHT EVO - the flexible 3-phase track spotlight series for perfect accent lighting. With single or double-flame spots, CCT options (3,000/4,000 K) and two total wattage options (18 W / 25 W), it provides the perfect setting for shops, galleries or showrooms. With UGR<19 and CRI>90, SIGHT EVO impresses with first-class light quality. The DALI option and uncomplicated installation make these lights perfect for versatile applications.

TECHNICAL DATA

Item no.	1010387
IP Code	IP20
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	DALI 2
Primary nominal voltage	220-240V ~50/60 Hz
Secondary power / voltage	700 mA
Safety class	II
Wattage	25 W
Maximum ambient temperature	35 °C
Number of luminaires at LS B16A	21
Number of luminaires at LS C16A	34
Level of inrush current	45 A
Duration of inrush current	280 µs
Lumen	3250 lm
Colour temperature	3000 Kelvin
Beam angle	60 °
Color	black
CRI	90
UGR ≤	16

Light Source

2432905	
---------	---

Service life	50000 h
Risk Group	1
Length	57.4 cm
Width	11.7 cm
Height	4 cm
Net weight	1.01 kg
Gross weight	1.43 kg
BIG WHITE Page	639