



## DOWNLIGHT VARIO 220 22 830/840 WH ML

DOWNLIGHT VARIA is your all-round lighting solution. A round, minimalist design. Available in two diameters: 22 cm and 29 cm. Easy to install. Equipped with a CCT switch, you can select your ideal colour temperature (3000 K and 4000 K). The wattage control allows you to easily adjust the light intensity - up to 3000 lumens for the 29cm version. There are also two models: on/off and with PIR sensor.

### TECHNICAL DATA

Item no.	1010397
Number of different light outlets	1
IP Code	IP20
Impact resistance class	IK 03
Assembly	Recessed
Assembly details	Ceiling
Number of through-wires	30
Primary nominal voltage	220-240V ~50/60 Hz
Secondary power / voltage	100/190 mA
Safety class	II
Wattage	9 W
Maximum ambient temperature	40 °C
Number of luminaires at LS B16A	36
Number of luminaires at LS C16A	60
Level of inrush current	18 A
Duration of inrush current	100 µs
Lumen	1150 / 1200 / 2200 / 2250 lm
Colour temperature	3000/4000 Kelvin
Beam angle	110 °
Color	white
CRI	80
UGR ≤	28

## Light Source

2432919	
---------	---

<b>Service life</b>	50000 h
<b>Risk Group</b>	1
<b>Height</b>	2.2 cm
<b>Diameter</b>	21.7 cm
<b>Net weight</b>	0.45 kg
<b>Gross weight</b>	0.59 kg
<b>Shape of cut-out</b>	TBD
<b>Installation depth</b>	3 cm
<b>Installation diameter</b>	19.5 cm