



## PANEL 60

Ceiling-mounted light, round, PHASE, 3000/4000K, 29-W, 90°, white

The new PANEL 60 - the efficient lighting solution for office and general areas. With a switchable colour temperature (3,000/4,000 K), CRI>90, improved energy efficiency and UGR<19, it meets all the requirements of modern workplaces. Ideal as a replacement for existing systems: simply replace and benefit immediately!

### TECHNICAL DATA

Item no.	1010422
Number of different light outlets	1
IP Code	IP20
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Assembly	Surface
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	Leading edge,trailing edge
Primary nominal voltage	220-240V ~50/60 Hz
Secondary power / voltage	750 mA
Safety class	I
Wattage	29 W
Maximum ambient temperature	45 °C
Number of luminaires at LS B16A	53
Number of luminaires at LS C16A	53
Level of inrush current	3.06 A
Duration of inrush current	224 µs
Lumen	3050 / 3300 lm
Colour temperature	3000/4000 Kelvin
Beam angle	90 °
Color	white

## Light Source

2432923	
---------	---

<b>CRI</b>	90
<b>UGR ≤</b>	19
<b>Service life</b>	50000 h
<b>Risk Group</b>	1
<b>Height</b>	6 cm
<b>Diameter</b>	60 cm
<b>Net weight</b>	4.8 kg
<b>Gross weight</b>	6.2 kg
<b>Shape of cut-out</b>	round
<b>Installation depth</b>	7 cm
<b>Installation diameter</b>	20 cm
<b>BIG WHITE Page</b>	181