



PANEL 60

Ceiling-mounted light, round, DALI, 3000/4000K, 29W, 90°, grey

The new PANEL 60 - the efficient lighting solution for office and general areas. With a switchable colour temperature (3,000/4,000 K), CRI>90, improved energy efficiency and UGR<19, it meets all the requirements of modern workplaces. Ideal as a replacement for existing systems: simply replace and benefit immediately!

TECHNICAL DATA

Item no.	1010425
Number of different light outlets	1
IP Code	IP20
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Assembly	Surface
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	DALI 2,Touch
Primary nominal voltage	220-240V ~50/60 Hz
Secondary power / voltage	750 mA
Safety class	I
Wattage	29 W
Maximum ambient temperature	45 °C
Number of luminaires at LS B16A	29
Number of luminaires at LS C16A	48
Level of inrush current	14.75 A
Duration of inrush current	256 µs
Lumen	3050 / 3300 lm
Colour temperature	3000/4000 Kelvin
Beam angle	90 °
Color	gray

Light Source

2432923	
---------	---

CRI	90
UGR \leq	19
Service life	50000 h
Risk Group	1
Height	6 cm
Diameter	60 cm
Net weight	4.8 kg
Gross weight	6.2 kg
Shape of cut-out	round
Installation depth	7 cm
Installation diameter	20 cm
BIG WHITE Page	181