



## 48V SYSTEM

Intrack LED driver, 48VDC, 100 W, incl. 300 cm connection cable for 220-240VAC and DALI through-wiring, white

Maximum minimalism and simple elegance: with an output of up to 100 watts, the LED driver is designed for flexible use in the 48V TRACK mounting tracks. Thanks to the four-wire 220V-240V / DALI through-wiring, controllable lighting concepts with particularly small tracks and spot-lights are easy to realise. The 3-metre cable supplied offers additional flexibility - ideal if the 48V rails are to be suspended.

## TECHNICAL DATA

Item no.	1010447
IP Code	IP20
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Assembly details	Ceiling,Wall
Primary nominal voltage	220-240V ~50/60 Hz
Secondary power / voltage	48 V
Safety class	II
Safety class	II
Wattage	115 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Number of luminaires at LS B16A	16
Number of luminaires at LS C16A	26
Level of inrush current	60 A
Duration of inrush current	200 µs
Color	white
Length	29.75 cm
Width	1.6 cm
Height	1.9 cm
Net weight	0.332 kg
Gross weight	0.36 kg

