




P-LIGHT

wall and ceiling-mounted light, rectangular, 6000K, 5.2W, white / transparent

P-LIGHT - reliable emergency and safety lighting for escape and rescue routes. With a 3-hour emergency operating time, self-test function, modern rechargeable battery technology and a 5-year guarantee, the lights ensure maximum safety. Pictogram sets and mounting sets are included in the scope of delivery - for fast, standard-compliant installation.



TECHNICAL DATA

Item no.	1010505
Number of different light outlets	1
IP Code	IP65
Impact resistance class	IK 07
Impact resistance	2 Joule
Assembly	Surface
Assembly details	Ceiling,Wall
Primary nominal voltage	220-240V ~50/60 Hz
Safety class	II
Wattage	5.2 W
Minimum ambient temperature	0 °C
Maximum ambient temperature	45 °C
Lumen	90 lm
Colour temperature	6000 Kelvin
Color	white/transparent
CRI	85
Service life	50000 h
Length	35.2 cm
Width	11.7 cm
Height	7.6 cm
Net weight	0.65 kg
Gross weight	0.766 kg

Accessories

1010499	P-LIGHT , set of 4, pictogram film, W: 10 H: 30 cm, green
1010498	P-LIGHT , installation kit for P-LIGHT 6W