




GLENOS® PRO

Recessed ceiling light, 1.2m, DALI, UGR19, 3000K, 75°, IP20, black

GLENOS® PRO is the new linear light range from SLV for sophisticated office and contract lighting. Whether pendant, surface mounted or recessed, all lights are glare-free (UGR<16/19) thanks to the micro-reflector and offer high efficiency of up to 134 lm/W with CRI>90. The lights can be connected seamlessly without light spillage, are halogen-free and guarantee uniform illumination with high visual comfort.



TECHNICAL DATA

Item no.	1010522
IP Code	IP20
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Assembly	Recessed
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	DALI, Touch
Number of through-wires	30
Primary nominal voltage	220-240V ~0/50/60 Hz
Secondary power / voltage	750 mA
Safety class	I
Wattage	30 W
Maximum ambient temperature	45 °C
Number of luminaires at LS B16A	29
Number of luminaires at LS C16A	48
Level of inrush current	15.875 A
Duration of inrush current	240 µs
Lumen	3650 lm
Colour temperature	3000 Kelvin
Beam angle	75 °
Color	black

Light Source



CRI	90
UGR ≤	19
Service life	100000 h
Risk Group	1
Length	131 cm
Width	7.3 cm
Height	7.8 cm
Net weight	4.2 kg
Gross weight	6.6 kg
Shape of cut-out	rectangular
Installation length	129.5 cm
Installation width	5.8 cm
Installation depth	11 cm
BIG WHITE Page	91