


## PAVANNO

1200/300 45 830/840/850 BK WH UGR19

PAVANNO: energy-efficient, durable, eligible for subsidies. With up to 190 lm/W, 100,000 h service life, UGR<19, multi-lumen/colour and DALI control, the luminaire is perfect for working environments such as offices, training rooms or healthcare facilities.



## TECHNICAL DATA

Item no.	1010580
IP Code	IP20
Impact resistance class	IK 02
Assembly	Recessed
Assembly details	Ceiling
Primary nominal voltage	220-240V ~0/50/60 Hz
Secondary power / voltage	500-1100 mA
Safety class	II
Wattage	17 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Number of luminaires at LS B16A	27
Number of luminaires at LS C16A	45
Level of inrush current	19.1 A
Duration of inrush current	220 µs
Lumen	2809 / 6538 lm
Colour temperature	3000/4000/5000 Kelvin
Beam angle	80 °
Color	black
CRI	80
UGR ≤	19
Service life	100000 h

## Light Source

2481882	
---------	---

<b>Risk Group</b>	1
<b>Length</b>	119.5 cm
<b>Width</b>	29.5 cm
<b>Height</b>	2 cm
<b>Net weight</b>	3.2 kg
<b>Gross weight</b>	3.4 kg