


## DOWNLIGHT P

230 40 HG 840 60 ML WH IP54


The DOWNLIGHT P combines a robust design with high efficiency: up to 170 lm/W, 80,000 h service life (L80B10) and multi-lumen function make it the ideal choice for offices, corridors or common areas. With a UGR value of 21 or 23, it provides pleasant light - available in versions with DALI control or as an on/off version.



## TECHNICAL DATA

Item no.	1010769
IP Code	IP54
Impact resistance class	IK 08
Primary nominal voltage	220-240V ~50/60 Hz
Secondary power / voltage	300-650 mA
Safety class	II
Wattage	12 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Number of luminaires at LS B16A	36
Number of luminaires at LS C16A	60
Level of inrush current	21 A
Duration of inrush current	180 µs
Lumen	2150 / 4410 lm
Colour temperature	4000 Kelvin
Beam angle	60 °
Color	white
CRI	80
Binning	3 SDCM
Service life	50000 h
Depth	9.5 cm
Diameter	23 cm

## Light Source

2194011		<b>Net weight</b>	1.14 kg
		<b>Gross weight</b>	1.31 kg
		<b>Shape of cut-out</b>	round
		<b>Installation diameter</b>	20 cm