

LALU® SET

pendant light, LED base, TETRA 36, PHASE, pendant length 200 cm, 2700/3000 K, 40°, black

The LALU® light range brings decorative variety to living spaces, hotels and restaurants: the mix & match concept allows different light bases and shades in trendy shapes and colours to be freely combined - perfect for customised lighting solutions in any interior. High-quality materials, sophisticated compatibility and easy assembly ensure long-lasting enjoyment. And when you need to get things done quickly, there are carefully curated, pre-configured kits. The result is a flexible light range that can be reinvented again and again.

TECHNICAL DATA

Item no.	1010791
Number of different light outlets	1
IP Code	IP20
Impact resistance class	IK 03
Impact resistance	0.35 Joule
Assembly	Surface
Dimmable	Yes
Dimming technology	trailing edge
Primary nominal voltage	220-240V ~50/60 Hz
Secondary power / voltage	500 mA
Safety class	I
Wattage	9.5 W
Maximum ambient temperature	35 °C
Number of luminaires at LS B16A	224
Number of luminaires at LS C16A	228
Level of inrush current	5 A
Duration of inrush current	100 µs
Lumen	700 / 800 lm
Colour temperature	2700/3000 Kelvin
Beam angle	40 °
Color	black
CRI	90

Light Source

	
--	---

Accessories

1010287	LALU® , pendant light, LED base, Mix&Match, surface mounted canopy, pendant length 200 cm, 2700/3000K, 40°, PHASE, black
1007529	LALU® TETRA 36 , Lampshade, Mix&Match, H:8.9 cm, black

Service life	50000 h
Height	19 cm
Diameter	36 cm
Pendant length	200 cm
Net weight	1.539 kg
Gross weight	2.274 kg