




WATERPROOF C

1200 57 830/840/850 ML DALI EM 3H IP66

The WATERPROOF moisture-proof luminaire offers energy-efficient lighting solutions in three performance classes, with up to 180 lm/W, IP66, IK08 and a service life of up to 100,000 hours. Thanks to tool-free cap opening and integrated through-wiring, installation is particularly quick. Optionally with DALI and sensor - ideal for industry, warehouses or underground car parks.



TECHNICAL DATA

| | |
|---------------------------------|-----------------------|
| Item no. | 1010818 |
| IP Code | IP66 |
| Impact resistance class | IK 08 |
| Assembly | Surface |
| Assembly details | Ceiling,Wall |
| Dimmable | Yes |
| Dimming technology | DALI |
| Primary nominal voltage | 220-240V ~0/50/60 Hz |
| Secondary power / voltage | 200-350 mA |
| Safety class | I |
| Wattage | 21 W |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 40 °C |
| Number of luminaires at LS B16A | 41 |
| Number of luminaires at LS C16A | 66 |
| Level of inrush current | 27.8 A |
| Duration of inrush current | 150 µs |
| Lumen | 3256 / 6137 lm |
| Colour temperature | 3000/4000/5000 Kelvin |
| Beam angle | 120 ° |
| Color | gray |
| UGR ≤ | 27 |

Light Source

| | |
|---------|---|
| 2481889 |  |
|---------|---|

| | |
|---------------------|---------|
| Service life | 75000 h |
| Risk Group | 1 |
| Length | 120 cm |
| Width | 8 cm |
| Height | 7.4 cm |
| Net weight | 1.96 kg |
| Gross weight | 2.13 kg |