




WATERPROOF P

1500 81 830/840/850 ML IP66

The WATERPROOF moisture-proof luminaire offers energy-efficient lighting solutions in three performance classes, with up to 180 lm/W, IP66, IK08 and a service life of up to 100,000 hours. Thanks to tool-free cap opening and integrated through-wiring, installation is particularly quick. Optionally with DALI and sensor - ideal for industry, warehouses or underground car parks.



TECHNICAL DATA

Item no.	1010825
IP Code	IP66
Impact resistance class	IK 08
Assembly	Surface
Assembly details	Ceiling,Wall
Primary nominal voltage	220-240V ~0/50/60 Hz
Secondary power / voltage	200-350 mA
Safety class	I
Wattage	26 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Number of luminaires at LS B16A	18
Number of luminaires at LS C16A	31
Level of inrush current	33.1 A
Duration of inrush current	168 µs
Lumen	4434 / 8123 lm
Colour temperature	3000/4000/5000 Kelvin
Beam angle	120 °
Color	gray
UGR ≤	27
Service life	100000 h
Risk Group	1

Light Source

2481888	
---------	---

Length	150 cm
Width	8 cm
Height	7.4 cm
Net weight	1.76 kg
Gross weight	1.98 kg