


# EASYLIGHT SPOT 500 457 935 | WB WH ML DALI2

**EASYLIGHT SPOT, 500 457 935 WB WH ML DALI2**

Whether for industrial buildings, supermarkets or logistics centres, the EASYLIGHT LED trunking system combines maximum flexibility, outstanding efficiency and high-output lighting technology in a modular system. The EASYLIGHT SPOT enables targeted accent lighting within the system. Offering a CRI >90, multiple colour temperatures and optional reflectors for different beam angles, it delivers precise light control. Available in black or white and optionally with DALI.




| | |
|---|---|
| **Item no.** | 1011542 |
| **IP Code** | IP20 |
| **Impact resistance class** | IK02 |
| **Dimmable** | true |
| **Dimming technology** | DALI 2 |
| **Primary nominal voltage** | 220-240V ~ 0/50/60Hz |
| **Secondary power / voltage** | 300-750 |
| **Safety class** | I |
| **Wattage** | 12 W |
| **Ambient temperature** | 85 |
| **Minimum ambient temperature** | -20°C |
| **Maximum ambient temperature** | 40°C |
| **Beam angle** | 36° |
| **Color** | white |
| **CRI** | 90 |
| **UGR ≤** | 19 |
| **LXXBXX data** | L80B10 |
| **Service life** | 50 000 h |
| **Risk Group** | 1 |
| **Length** | 50 cm |
| **Width** | 7.9 cm |
| **Height** | 18 cm |
| **Diameter** | 9 cm |
| **Net weight** | 1.66 kg |
| **Gross weight** | 1.78 kg |