


TRACK LINE S 3PH. 39 830/835/840 DWB ML | BK DALI

TRACK LINE S, 3~ Spot, 39 830/835/840 DWB ML BK DALI

The TRACK LINE S 3~ spot is a three-phase spotlight suitable for indoor use, for example in retail or exhibition areas. The luminaire provides a light output of 2300 to 4000 lumens and is equipped with a DALI 2 dimming function, allowing flexible light control. The housing is made of aluminium, complemented by PMMA optics, and measures 57.8 cm in length, 6.47 cm in width, and 7 cm in height. The protection rating is IP20, making it suitable for dust-protected, dry environments. The impact resistance corresponds to IK02 class. The luminaire is designed for professional use and offers a declared service life of 100,000 hours.



Item no.	1011583
IP Code	IP20
Impact resistance class	IK02
Dimmable	true
Dimming technology	DALI 2
Primary nominal voltage	220-240V ~ 50/60Hz
Secondary power / voltage	200-350mA
Safety class	I
Wattage	15 W
Ambient temperature	80
Minimum ambient temperature	-20°C
Maximum ambient temperature	40°C
Number of luminaires at LS B16A	19.0
Number of luminaires at LS C16A	32.0
Level of inrush current	16.63 A
Duration of inrush current	330 µs
Beam angle	120°
Color	black
CRI	80
LXXBXX data	L80B10
Service life	100 000 h
Length	57.8 cm
Width	6.5 cm
Height	7 cm
Net weight	0.71 kg
Gross weight	0.81 kg