


TRACKSPOT C 3PH 55 940 | NB ML BK DALI

TRACKSPOT C 3PH, 55 940 NB ML BK DALI

The TRACKSPOT C is a versatile LED spotlight solution for 3-phase tracks and is ideal for retail and commercial applications. With its multi-lumen function, various beam angles and optional DALI control, it enables flexible adaptation to different lighting requirements and ensures efficient, needs-based illumination.



Light source

2194011	A B

Item no.	1011821
Number of different light outlets	1
IP Code	IP20
Impact resistance class	IK02
Assembly	Track
Assembly details	Ceiling,Wall,
Dimmable	true
Dimming technology	DALI 2
Primary nominal voltage	220-240V ~ 0/50/60Hz
Secondary power / voltage	300-1050mA
Safety class	II
Wattage	12 W
Minimum ambient temperature	-20°C
Maximum ambient temperature	35°C
Number of luminaires at LS B16A	27.0
Number of luminaires at LS C16A	44.0
Level of inrush current	18 A
Duration of inrush current	3 µs
Beam angle	24°
Color	black
CRI	90
UGR ≤	25
LXXBXX data	L70B10
Service life	50 000 h
Length	10.5 cm
Width	23.8 cm
Height	14 cm
Net weight	0.72 kg
Gross weight	0.9 kg