




## TRUKKO 90

wall light, LED, 3000K, chrome/white, H 90 cm, incl. LED driver

The elegant and slender form of the TRUKKO 90 wall light is made from white plastic with chrome-plated zinc cast components and provides a strong design character with high recognition value. The integrated Premium LED offers pleasing lighting effects in two different intensities. The in-built LED driver allows it to be directly connected to the 230V mains supply.



## TECHNICAL DATA

|                             |                   |
|-----------------------------|-------------------|
| Item no.                    | 149772            |
| IP Code                     | IP 44             |
| Impact resistance class     | IK 03             |
| Impact resistance           | 0.35 Joule        |
| Assembly                    | Surface           |
| Assembly details            | Wall              |
| Primary nominal voltage     | 220-240V ~50/60Hz |
| Secondary power / voltage   | 500 mA            |
| Safety class                | I                 |
| Wattage                     | 12 W              |
| Ambient temperature         | 30 °C             |
| Minimum ambient temperature | -40 °C            |
| Maximum ambient temperature | 30 °C             |
| Level of inrush current     | 4.7 A             |
| Duration of inrush current  | 30 µs             |
| Stroboscopic effect (SVM)   | 0.01              |
| Lumen                       | 1040 lm           |
| Colour temperature          | 3000 Kelvin       |
| Beam angle                  | 120 °             |
| Color                       | chrome            |
| CRI                         | 90                |
| LXXBXX data                 | L70B50            |

## Light Source

|        |                                                                                   |                       |
|--------|-----------------------------------------------------------------------------------|-----------------------|
| 916396 |  |                       |
|        |                                                                                   | <b>Service life</b>   |
|        |                                                                                   | 50000 h               |
|        |                                                                                   | <b>Risk Group</b>     |
|        |                                                                                   | 0                     |
|        |                                                                                   | <b>Length</b>         |
|        |                                                                                   | 90 cm                 |
|        |                                                                                   | <b>Width</b>          |
|        |                                                                                   | 4 cm                  |
|        |                                                                                   | <b>Depth</b>          |
|        |                                                                                   | 5 cm                  |
|        |                                                                                   | <b>Net weight</b>     |
|        |                                                                                   | 0.87 kg               |
|        |                                                                                   | <b>Gross weight</b>   |
|        |                                                                                   | 1.097 kg              |
|        |                                                                                   | <b>BIG WHITE Page</b> |
|        |                                                                                   | 332                   |