




## BIMA 1

spot for 240V 3-phase track, single-headed, QPAR51,-round, silver-grey max. 50W, incl. 3-phase adapter

Adjustable high-voltage spot BIMA 1 with suitable adapter for the 240V 3-phase track system. The luminaire is made of aluminium and, thanks to the GU10 socket, is suitable for both halogen and LED lamps.



## TECHNICAL DATA

|                           |                         |
|---------------------------|-------------------------|
| Item no.                  | 152242                  |
| Socket                    | GU10                    |
| Number of sockets         | 1                       |
| Tilt range                | 200 °                   |
| Horizontal rotation range | 350 °                   |
| Rotating or tilting       | rotary Bar and tiltable |
| IP Code                   | IP 20                   |
| Assembly                  | Surface                 |
| Assembly details          | Ceiling, Track Ceiling  |
| Primary nominal voltage   | 220-240V ~50/60Hz       |
| Safety class              | II                      |
| Wattage                   | 50 W                    |
| Color                     | grey                    |
| Light outlet              | direct                  |
| Length                    | 8 cm                    |
| Height                    | 15 cm                   |
| Diameter                  | 6 cm                    |
| Net weight                | 0.293 kg                |
| Gross weight              | 0.358 kg                |
| BIG WHITE Page            | 541                     |

## Recommended lamp

|         |                                                        |
|---------|--------------------------------------------------------|
| 1005075 | LED lightbulb QPAR51 ,<br>GU10, 2700K, grey            |
| 1005081 | LED lightbulb QPAR51 ,<br>GU10, 4000K, grey            |
| 1005273 | QPAR51 GU10 , LED<br>light, 6W 2200 2700K<br>CRI90 36° |
| 1005078 | LED lightbulb QPAR51 ,<br>GU10, 3000K, grey            |