




## KARPO

**recessed fitting, single-headed, LED, 3000K, white, flat canopy, 7.5W**

KARPO series lights are available in white and black. It has a spot in a cylindrical shape which can be individually aligned via the hinge on the flat canopy. The swivel and tilting range allows you to optimally light up the room. The integrated premium LEDs provide high energy efficiency. In addition, the luminaire has a high colour rendering index of over 90. To operate, the single-headed FRAME Spots needs a suitable constant current driver rated at 500mA.



## TECHNICAL DATA

|                             |                         |
|-----------------------------|-------------------------|
| Item no.                    | 152381                  |
| Rotating or tilting         | rotary Bar and tiltable |
| IP Code                     | IP 20                   |
| Assembly                    | Recessed                |
| Assembly details            | Ceiling,Wall            |
| Secondary power / voltage   | 500 mA                  |
| Safety class                | III                     |
| Wattage                     | 7.5 W                   |
| Maximum ambient temperature | 40 °C                   |
| Lumen                       | 470 lm                  |
| Colour temperature          | 3000 Kelvin             |
| Beam angle                  | 40 °                    |
| Color                       | white                   |
| CRI                         | 90                      |
| LXXBXX data                 | L70B50                  |
| Service life                | 30000 h                 |
| Light distribution          | rotational symmetric    |
| Light outlet                | direct                  |
| Length                      | 15.2 cm                 |
| Height                      | 5.5 cm                  |
| Diameter                    | 3 cm                    |
| Net weight                  | 0.177 kg                |

## Light Source

|        |                                                                                   |
|--------|-----------------------------------------------------------------------------------|
| 916381 |  |
|--------|-----------------------------------------------------------------------------------|

## Accessories

|         |                                          |
|---------|------------------------------------------|
| 1007226 | LED driver 21W 500mA                     |
| 1007227 | LED driver 20W 350mA-<br>/500mA PHASE    |
| 1007229 | LED driver 25W 150-700-<br>mA DALI TOUCH |

|                       |          |
|-----------------------|----------|
| Gross weight          | 0.281 kg |
| Shape of cut-out      | round    |
| Installation depth    | 2 cm     |
| Installation diameter | 7 cm     |
| BIG WHITE Page        | 232      |