




KALU TRACK

spot for 240V 3-phase track, LED, 3000K, round, black, incl. 3-phase adapter

Adjustable KALU TRACK spotlight with suitable adapter for the 3-circuit 240V track system. Designed as an extension of the popular KALU series, this new spotlight takes on the shape of the product family. The built-in LED module guarantees high light output with low power consumption. To meet all lighting requirements, versions with G53 and GX53 sockets for the 1- and 3-circuit systems are available. This luminaire contains built-in LED lamps.



TECHNICAL DATA

Item no.	152600
Number of different light outlets	1
Rotating or tilting	rotary Bar and tiltable
IP Code	IP 20
Assembly	Surface
Assembly details	Ceiling,Track Ceiling,Track Wall,Wall
Dimmable	Yes
Dimming technology	Leading edge,trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Safety class	II
Wattage	13 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	35 °C
Level of inrush current	3 A
Duration of inrush current	10 µs
Lumen	970 lm
Colour temperature	3000 Kelvin
Beam angle	95 °
Color	black
CRI	80
LXXBXX data	L70B50
Service life	25000 h

Light Source

703130		Length	13.5 cm
		Height	17 cm
		Diameter	10.5 cm
		Net weight	0.497 kg
		Gross weight	0.607 kg
		BIG WHITE Page	540