




Technical data

Voltage	100-240 VAC 50/60 Hz
Standby system effect	<0.5W
Load type	Capacitive (LED), ohmic load
Max. load	400W LED per channel
Push input, P	Yes, 230Vac P1 and P2
Power metering,W	Total for both channels
Exterior dimension	L: 42 mm, W: 38 mm, H: 16 mm
Possibility of through wiring	Yes
IP rating	IP20
Material	Aluminium, plastic
Environment	Indoors
Warranty	5 years
Approvals	CE



100-240 Vac

2x400W LED

2 ch relay

IP20

House icon

Head icon

340

CE

RoHS

No flame icon

Product information

- Zigbee relay with 2 channels (based on Zigbee 3.0 protocol)
- Each output can be controlled by separate push switches
- Works with Homey
- On/Off Relay: LED 2 x 400W
- Input and output with screw terminals
- Compatible with various types of switches: momentary, toggle - 230V
- Radio Frequency: 2.4GHz
- Mini size, easy to be installed into a standard 68 x 68 mm wall box
- Power metering via Homey
- Compatible with universal Zigbee gateways
- Over load /over heat protection
- **DO NOT expose the device to moisture**
- **Do NOT install the device, when connected to power**

Item no.	EAN no.	Environment
98423251	5704629006522	indoor

NB: Always use cables of a type approved for permanent installation according to the current legislation. If the cables are in contact with the lamp cover, use cables with an operating temperature of at least 70° C.